

Type	Interflow PAK 60/60	Interflow PAK 60/90	Interflow PAK 60/120	Interflow PAK 60/150	Interflow PAK 60/180
Material cabinet	HPL	HPL	HPL	HPL	HPL
Material worktop	HPL	HPL	HPL	HPL	HPL
Material workspace	HPL	HPL	HPL	HPL	HPL
Dim. external body (wxdxh)	640 x 750 x 1160 mm	945 x 750 x 1160 mm	1252 x 750 x 1160 mm	1556 x 750 x 1160 mm	1862 x 750 x 1160 mm
Dim. workspace (wxdxh)	616 x 610 x 600 mm	921 x 610 x 600 mm	1228 x 610 x 600 mm	1532 x 610 x 600 mm	1838 x 610 x 600 mm
Installation fits through 800 mm door	Yes	Yes	Yes	Yes	Yes
Height worktop w.r.t. floor	760 / 940 mm	760 / 940 mm	760 / 940 mm	760 / 940 mm	760 / 940 mm
Total height including frame sit / stand	1920 / 2100 mm	1920 / 2100 mm	1920 / 2100 mm	1920 / 2100 mm	1920 / 2100 mm
Weight (top cabinet)	70 kg	100 kg	115 kg	135 kg	150 kg
Electric high-low frame	Optional	Optional	Optional	Optional	Optional
One-piece workspace	Yes	Yes	Yes	Yes	Yes
Full service front side	Yes	Yes	Yes	Yes	Yes
Adjustable control of desired air velocity	0,20 – 0,45 m/s	0,20 – 0,45 m/s	0,20 – 0,45 m/s	0,20 – 0,45 m/s	0,20 – 0,45 m/s
Fan type	Direct current motor	Direct current motor	Direct current motor	Direct current motor	Direct current motor
Voltage	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Fuse	16 A	16 A	16 A	16 A	16 A
Electricity consumption	0,9 A	1,0 A	1,1 A	1,2 A	1,65 A
Power consumption	100 W	110 W	115 W	120 W	252 W
Brightness	> 750 Lux	> 1000 Lux - dimmable	> 1000 Lux - dimmable	> 1000 Lux - dimmable	> 1000 Lux - dimmable
Lighting type	LED – on / off	LED - dimmable	LED - dimmable	LED - dimmable	LED - dimmable
Control	Stepless regulation	Touchscreen / PLC technologie	Touchscreen / PLC technologie	Touchscreen / PLC technologie	Touchscreen / PLC technologie
Socket 230 V	Optional	Optional	Optional	Optional	Optional
Side windows	Optional	Optional	Optional	Optional	Optional
Connectivity package	Optional	Optional	Optional	Optional	Optional
Weighing balance facilities integrated into the worktop	Optional	Optional	Optional	Optional	Optional
Acoustic level	47 dB(A)	47 dB(A)	47 dB(A)	47 dB(A)	47 dB(A)
Ergonomic leg space	Yes	Yes	Yes	Yes	Yes
Ergonomic seat angle 12 degrees	Yes	Yes	Yes	Yes	Yes
Warranty	1 year	1 year	1 year	1 year	1 year
Customer-specific requirements	Negotiable / own factory	Negotiable / own factory	Negotiable / own factory	Negotiable / own factory	Negotiable / own factory
Filter grade					
Pre-filter, NEN-EN-ISO 16890	G3	G3	G3	G3	G3
Absolute filter, EN1822	H14	H14	H14	H14	H14

Type	Interflow PAK 60/60	Interflow PAK 60/90	Interflow PAK 60/120	Interflow PAK 60/150	Interflow PAK 60/180
Material cabinet	HPL	HPL	HPL	HPL	HPL
Material worktop	HPL	HPL	HPL	HPL	HPL
Material workspace	HPL	HPL	HPL	HPL	HPL
Dim. external body (wxdxh)	640 x 482 x 850 mm	945 x 750 x 1460 mm	1252 x 750 x 1460 mm	1556 x 750 x 1460 mm	1862 x 750 x 1460 mm
Dim. workspace (wxdxh)	616 x 280 x 390 mm	921 x 610 x 900 mm	1228 x 610 x 900 mm	1532 x 610 x 900 mm	1838 x 610 x 900 mm
Installation fits through 800 mm door	Yes	Yes	Yes	Yes	Yes
Height worktop w.r.t. floor	760 / 940 mm	760 / 940 mm	760 / 940 mm	760 / 940 mm	760 / 940 mm
Total height including frame sit / stand	1920 / 2100 mm	1920 / 2100 mm	1920 / 2100 mm	1920 / 2100 mm	1920 / 2100 mm
Weight (top cabinet)	50 kg	120 kg	130 kg	165 kg	195 kg
Electric high-low frame	Optional	Optional	Optional	Optional	Optional
One-piece workspace	Yes	Yes	Yes	Yes	Yes
Full service front side	Yes	Yes	Yes	Yes	Yes
Adjustable control of desired air velocity	0,20 – 0,45 m/s	0,20 – 0,45 m/s	0,20 – 0,45 m/s	0,20 – 0,45 m/s	0,20 – 0,45 m/s
Fan type	Direct current motor	Direct current motor	Direct current motor	Direct current motor	Direct current motor
Voltage	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Fuse	16 A	16 A	16 A	16 A	16 A
Electricity consumption	0,8 A	0,52 A	1,2 A	1,5 A	1,6 A
Power consumption	85 W	90 W	120 W	150 W	200 W
Brightness	> 750 Lux	> 1000 Lux - dimmable	> 1000 Lux - dimmable	> 1000 Lux - dimmable	> 1000 Lux - dimmable
Lighting type	LED – on / off	LED - dimmable	LED - dimmable	LED - dimmable	LED - dimmable
Control	Stepless regulation	Touchscreen / PLC technologie	Touchscreen / PLC technologie	Touchscreen / PLC technologie	Touchscreen / PLC technologie
Socket 230 V	Optional	Optional	Optional	Optional	Optional
Side windows	Optional	Optional	Optional	Optional	Optional
Connectivity package	Optional	Optional	Optional	Optional	Optional
Weighing balance facilities integrated into the worktop	Optional	Optional	Optional	Optional	Optional
Acoustic level	47 dB(A)	47 dB(A)	47 dB(A)	47 dB(A)	47 dB(A)
Ergonomic leg space	Yes	Yes	Yes	Yes	Yes
Ergonomic seat angle 12 degrees	Yes	Yes	Yes	Yes	Yes
Warranty	1 year	1 year	1 year	1 year	1 year
Customer-specific requirements	Negotiable / own factory	Negotiable / own factory	Negotiable / own factory	Negotiable / own factory	Negotiable / own factory
Filter grade					
Pre-filter, NEN-EN-ISO 16890	G3	G3	G3	G3	G3
Absolute filter, EN1822	H14	H14	H14	H14	H14

Interflow

De Stek 15
1771 SP Wieringerwerf
Nederland
T +31 (0)227 60 28 44
E info@interflow.nl
W www.interflow.nl

Want to know more about the possibilities?

Please contact our advisor:

Arjan van der Scheer
M +31 (0)653 54 12 05
E arjan.vander.scheer@interflow.nl