

Interflow's laminar airflow units excel at providing person protection, product protection or both. Interflow has fifty years of experience in the engineering, construction, validation and management of these products. Interflow's laminar airflow units are rated best for quality and value for money. In addition, our customers are enthusiastic about the delivery reliability and service. They also give the highest rating on commercial and technical support.



Down flow unit Product protection

The down flow unit, type IF/DF from Interflow is characterised by compact construction, great ease of operation and is solid and reliable. The unit is flexible in use. You can hang the down flow unit above your production facility or place it on a base to create a conditioned workspace with one or more units.

- Manufactured from high-quality HPL material
- Standard stainless steel worktop (SS 304)
- Completely smooth executed both internally and externally
- Customised solutions possible
- · Installation and validation on site
- Can be installed singly or in series

Safe to Use

- Complies with IEST-RP-CC002.4 guideline
- Deployable in accordance with ISO and GMP standards
- CE-marking
- Fail-safe design
- Hermetic bonding
- Meets at least Class 5 according to ISO 14644-1

Comfortable


- Homogeneous light
- Low heat load
- · Ergonomic top design

User-friendly

- · Easy to operate
- Effortless cleaning
- Pre-filters at the front are easy to replace
- Optimal air distribution
- Plug-and-Play
- Absolute filter can be replaced from the bottom

Sustainable

- Up to 70% reduction in energy consumption thanks to energy-saving EC-motor
- Energy-saving LED lighting
- Day and night switch as standard



The cross-section above shows the working of the down flow unit